

Link to the product: <https://pokolimited.co.uk/acryl-car-line-p-10.html>



## Acryl Car Line

Price	<b>9.99 GBP</b>
Availability	<b>Always on stock</b>
Shipping time	<b>3 days</b>

### Product description

Extra fast drying acrylic lacquer (short car's line) used for small paint corrections and maintenance as well as universal multi-purpose product in 5 most common colours. Especially suitable for painting machines and their parts, equipment, aluminium constructions, tools, vehicles, steel furniture etc. Also used for surfaces made of wood, ceramics, glass, wicker, cardboard and some plastics.

#### Notice:

For surfaces made of PUR, PS, PA, EPDM, ABS, GfK, Hart - PCV use Plastic Primer DECO COLOR previously. Best result when applied at 10-25°C.

Extremely fast drying time up to 5 minutes !

Touch dry: 15-20 min; Hardened: 16-20 h

Efficiency 2-2,5 m<sup>2</sup> 150ml : 0,8 m<sup>2</sup> depending on colour and type of surface by one application

Very good covering

High gloss, Additionally black in matt finish

Creates hard coating resistant to scratches and hits

Anticorrosive properties

Petrol resistance

5 basic colours in RAL system

For indoor and outdoor use

Capacity 500ml or 150ml

#### Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

#### Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

#### How to use:

---

Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

### This product has additional options:

**Color:** Acryl Car Line Black , Acryl Car Line Black\_matt , Acryl Car Line Aluminium , Acryl Car Line White , Acryl Car Line Transparent , Acryl Car Line Black 150ml (- 0.60 GBP ) , Acryl Car Line Black\_matt 150ml (- 0.60 GBP ) , Acryl Car Line Aluminium 150ml (- 0.60 GBP ) , Acryl Car Line White 150ml (- 0.60 GBP ) , Acryl Car Line Transparent 150ml (- 0.60 GBP )

### Color chart

