Link to the product: https://pokolimited.co.uk/acryl-primer-1k-p-12.html



Acryl Primer 1K

| Price | 9.99 GBP |
|---------------|-----------------|
| Availability | Always on stock |
| Shipping time | 3 days |

Product description

Fast drying 1K Acryl Primer with perfect covering properties. Protects against corrosion. Improves adhesion of top coat. Compatible with all paint systems (alkyd, acrylic, nitro-combination) water and solvent based. Designed for priming surfaces made of metal, wood, aluminium, stone, concrete, and some plastic surfaces. Wide range of application hobby and professional works: at home, garden, automotive and industry.

Notice:

For surfaces made of PUR, PS, PA, EPDM, ABS, GfK, Hart - PCV use Plastic Primer DECO COLOR previously. Best result when applied at 10-25°C.

Protects against corrosion Very good covering Possibility of grinding when wet or dry Petrol resistance Short drying time: 5-8 min

Touch dry: 15-20 min; Hardened: 10-14 h

Efficiency 2-2,5 m² 150ml: 0,8 m² depending on colour and type of surface by one application

4 colours offer: gray, white, red oxide and black

Matt finish of painted surface For indoor and outdoor use Capacity 500 ml or 150 ml

Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. Surface should be grinded with fine-grained sandpaper (e.g. P600).

How to use:

Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

This product has additional options:

Color: Acryl Primer 1K Grey , Acryl Primer 1K White , Acryl Primer 1K Red oxide , Acryl Primer 1K Black , Acryl Primer 1K Grey 150ml (- 0.60 GBP), Acryl Primer 1K White 150ml (- 0.60 GBP), Acryl Primer 1K Red oxide 150ml (- 0.60 GBP), Acryl Primer 1K Black 150ml (- 0.60 GBP)

Color chart

