



# Decoration matt - universal paint

Price	<b>9.49 GBP</b>
Availability	<b>Always on stock</b>
Shipping time	<b>3 days</b>

## Product description

New line of unique decorative lacquers with matt finish.

Universal synthetic solvent-based lacquer for painting surfaces made of metal, wood, ceramics, glass, wicker, cardboard, fabrics, fresh and artificial flowers, and some plastics. Wide range of application hobby and professional works: at home, garden, automotive and industry.

Notice. For surfaces made of PUR, PS, PA, EPDM, ABS, GfK, Hart - PCV use Plastic Primer DECO COLOR previously.

Best result when applied at 10-25°C.

### Notice:

For surfaces made of PUR, PS, PA, EPDM, ABS, GfK, Hart - PCV use Plastic Primer DECO COLOR previously. Best result when applied at 10-25°C.

Matt finish of painted surface

Perfect covering

Short drying time: 10-15 min

Touch dry: 30-40 min; Hardened: 24 h

Efficiency 1,5-2 m<sup>2</sup> depending on colour and type of surface by one application

High resistance to abrasion and weather conditions

Variety of colours: over 20 most popular colours in RAL system

For indoor and outdoor use

Capacity 400 ml

### Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

### Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

### How to use:

---

Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

This product has additional options:

**Color:** RAL 1015 Ivory\_matt , RAL 1023 Yellow\_traffic\_matt , RAL 2004 Orange\_matt , RAL 3000 Red\_fire\_matt , RAL 3005 Red\_wine\_matt , RAL 4003 Pink\_matt , RAL 4005 Violet\_matt , RAL 4006 Fuchsia\_matt , RAL 5005 Blue\_signal\_matt , RAL 5015 Blue\_sky\_matt , RAL 6018 Green\_light\_matt , RAL 6029 Green\_mint\_matt , RAL 7001 Grey\_matt , RAL 7016 Anthracite\_matt , RAL 7035 Grey\_light\_matt , RAL 8019 Brown\_matt , RAL 9005 Black\_matt , RAL 9016 White\_traffic\_matt , RAL 0000 Transparent\_matt , Parma Trendy\_Violet\_matt

## Color chart

