Data current as of: 16-11-2026 02:01

Link to the product: https://pokolimited.co.uk/decoration-universal-paint-p-2.html



Decoration - universal paint

Price	**8.99 GBP**
Availability	**Always on stock**
Shipping time	**3 days**

Product description

Universal synthetic solvent-based paint for painting surfaces made of metal, wood, ceramics, glass, wicker, cardboard, fabrics, fresh and artificial flowers, and only some plastics. Wide range of application hobby and professional works: at home, garden, automotive and industry. Especially practical for works of art and decoration. Easy to use.

>>> https://www.youtube.com/watch?v=fByHYY8NcZk

Notice:
For surfaces made of PUR, PS, PA, EPDM, ABS, GfK, Hart – PCV use
Plastic Primer DECO COLOR previously. Best result when applied at 10-25°C.

Very good covering of painted surface
High gloss; Additionally: gold and aluminium in satin finish; black and white also in matt finish
Short drying time: 10-15 min
Touch dry: 30-40 min; Hardened: 24 h
Efficiency 1,5-2 m² depending on colour and type of surface by one application
High resistance to abrasion and weather conditions
Variety of colours: more than 30 most common colours in RAL system
For indoor and outdoor use
Capacity 400 ml

Usage:

Before applying read carefully instructions on the container and
use according to the manufacturer’s recommendations.

Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

How to use:

Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer,

wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

+

This product has additional options:

Color: RAL 1015 Ivory , RAL 1023 Yellow traffic , RAL 1028 Yellow melon , RAL 2004 Orange , RAL 3000 Red fire , RAL 3003 Red ruby , RAL 3004 Red purple , RAL 3020 Red , RAL 4003 Pink , RAL 4005 Violet , RAL 4006 Fuchsia , RAL 5002 Blue ultramarine , RAL 5003 Blue sapphire , RAL 5010 Blue gentian , RAL 5015 Blue sky , RAL 5021 Turquoise , RAL 6005 Green dark , RAL 6018 Green light , RAL 6029 Green mint , RAL 7001 Grey , RAL 7016 Anthracite , RAL 7035 Grey light , RAL 8003 Brown clay , RAL 8004 Brown cooper , RAL 8011 Brown nut , RAL 8017 Brown chocolate , RAL 9005 Black , RAL 9005 Black_matt finish , RAL 9006 Aluminium_satin finish , RAL 9010 White , RAL 9010 White_matt finish , RAL 0000 Transparent , RAL 0000 Gold_satin finish

Color chart

