Data current as of: 28-11-2026 18:54

Link to the product: https://pokolimited.co.uk/eco-revolution-clear-water-based-clear-coat-p-50.html



Eco Revolution Clear - water based clear coat

Price	**9.49 GBP**
Availability	**Always on stock**
Shipping time	**3 days**
Number	**5906739723003**

Product description

High quality acrylic water-based clear coat
Perfect fits for use directly on styrofoam and for painting surfaces made of metal, wood, ceramics, glass, wicker, cardboard, fabrics, fresh and artificial flowers, and some plastics.
Lacquer without aggressive odor, environmentally and human friendly.
Product dedicated for artists and decorators. Wide range of application hobby and professional works: at home, garden, automotive and industry.

Notice:

For surfaces made of PUR, PS, PA, EPDM, ABS, GfK, Hart – PCV use
Plastic Primer DECO COLOR previously. Best result when applied at 10-25°C.

Special, high covering of painted surface
High gloss; Additionally black and white also in matt finish
Intensity of colours
Short drying time: 20-30 mins
Touch dry: 60 min; Hardened: after 24 h
All the adjusts can be done up to 20 min
Water resistance is achieved after 5-6 days
Efficiency 1,5-2 m² depending type of surface by one application
Hard acrylic coating resistant to abrasion and mechanical damages
For indoor and outdoor use
Capacity 400 ml

Usage:

Before applying read carefully instructions on the container and use according to the manufacturer’s recommendations.

Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

How to use:

Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.