Link to the product: https://pokolimited.co.uk/fluorescent-p-60.html



Fluorescent

Price	9.99 GBP
Availability	Always on stock
Shipping time	3 days

Product description

Special paint with a high content of fluorescent pigments which make them more intensive and have light reflecting properties. Recommended to painting inscriptions and warning signs. Marking dangerous places to emphasize their visibility. Used successfully at surveying works and forestry, as well as in decorating, at florists can be used for fresh and artificial flowers.

>>> https://www.youtube.com/watch?v=g-8L2gOachs

Notice:

Fluorescent paint is **not** a phosphorescent one (it does not glow in the dark). Applying primer white previously helps to get extra high bright visibility. Covered with clear coat improves weather conditions resistance. Best result when applied at 10-25°C.

Light reflecting properties
Covering depends on usage of white primer
Short drying time: 5-10 min
Touch dry: 20-30 min; Hardened: 18-24 h
Efficiency 1,5-2 m² depending on colour and type of surface by one application
Limited resistance to UV and weather conditions
Offer in 7 most common colours
For indoor and outdoor use
Capacity 400 ml

Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

How to use:

Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air

humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

Color chart

