

Link to the product: <https://pokolimited.co.uk/megabamp-bumper-paint-p-17.html>



## Megabamp - bumper paint

Price	<b>9.99 GBP</b>
Availability	<b>Always on stock</b>
Shipping time	<b>3 days</b>

### Product description

Professional fast drying lacquer for painting of plastic parts and bumpers which does not change the primary structure of surface. Also used for painting of dashboards and spoilers made of PP and ABS. Product for renewing restoring and refurbishing all plastic parts of the car.

#### Notice:

Best result when applied at 10-25°C.

Faster drying time up to 5 minutes !

Touch dry: 15-20 min; Hardened: 16-20 h

Efficiency 2-2,5 m<sup>2</sup> depending on colour and type of surface by one application

Very good covering

Doesn't change the structure of painted surface

Creates hard coating resistant to scratches and hits

Petrol resistance

3 basic bumper colours in RAL system

For indoor and outdoor use

Capacity 500 ml

#### Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

#### Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating.

#### How to use:

Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

---

This product has additional options:

**Color:** RAL 7043 Grey dark , RAL 7046 Grey light , RAL 9005 Black

## Color chart

