

Link to the product: <https://pokolimited.co.uk/military-paint-army-camouflage-p-39.html>



# Military Paint - army camouflage

Price	<b>8.99 GBP</b>
Availability	<b>Always on stock</b>
Shipping time	<b>3 days</b>

## Product description

Anti-reflective paint used as well to military camouflage, as to renovate military equipment. Wide range of application in masking on hunting, but most of all to mask the equipment in very popular ASG games like MilSim.

Military simulations also known informally as war games is a military action organized by civilians, as a form of outdoor recreation. The most popular forms of MilSim are extended variety of paintball games and airsoft. During such games replicas of weapons are used, the most common is Air Soft Gun or (less) paintball guns or LaserTag (especially in countries where the law forbids usage of airsoft replicas). New line of Military Paint fulfill expectations of hobbyists.

Due to specially selected colours of Military Paint you are able to make a professional camouflage of your military equipment or make its renovation.

### Camouflage system of MILITARY PAINT 3 in 1:

1. Anticorrosive protection of painted surface
2. Paints in 11 most common colours
3. External factors protection

### Notice:

Paint is compatible with all paint systems (alkyd, acryl, nitro-combination) water and solvent based.

High adhesive

Short drying time up to 8 minutes!

Touch dry: 15-20 min; Hardened: 10-14 h

Efficiency 1,5-2 m<sup>2</sup> depending on colour and type of surface by one application

Matt finish of painted surface

Variety of 11 most common colours of military camouflage

For indoor and outdoor use

Capacity 400 ml

### Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

### Recommended substrate conditions:

Don't use any priming paint.

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle,

---

which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

### How to use:

Don't use any priming paint previously. Do not cover already painted surface by any other paint. Apply product at temperature about 10 - 25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

### This product has additional options:

**Color:** RAL 1001 Sand Khaki , RAL 1019 Desert Storm , RAL 6003 Olive Green , RAL 6014 Olive Drap , RAL 6031 Forest Green , RAL 7013 Brown Uniform , RAL 7016 Anthracite , RAL 7038 Grey , RAL 8027 Mud Brown , RAL 9010 White , RAL 9021 Flat Black

### Color chart

