Data current as of: 02-11-2026 20:42

Link to the product: https://pokolimited.co.uk/renovator-appliance-p-45.html



Renovator Appliance

Price	**8.99 GBP**
Availability	**Always on stock**
Shipping time	**3 days**
Number	**5906739730056**

Product description

Fast drying acrylic lacquer for painting and renovation of: fridges, refrigerators, washing machines and other household appliances. Doesn’t become yellow, has good thermal conductivity. Perfect for renovation of outside metal layers of houlsehold appliances. Provides smooth, durable sufrace, you can easly clean.

Heat resistance up to 100°C
Directly to household appliances
Resistant to moisture and rust
Creates smooth, glossy surface
Most popular colour: pure white RAL 9016
Fast drying time: 5 minutes !
Touch dry: 15-20 min
Hardened: 16-20 h
Efficiency 1,5 – 2 m^2 depending on type of surface by one application
Hard acrylic film resistant to water and abrasion
For indoor and outdoor use
Capacity 400 ml

Usage:

Before applying read carefully instructions on the container and use according to the manufacturer’s recommendations.

Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

How to use:

You can easily cover already painted surface by any other paint, grinding previously. Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.