

Link to the product: <https://pokolimited.co.uk/renovator-radiator-p-44.html>



# Renovator Radiator

Price	<b>8.99 GBP</b>
Availability	<b>Always on stock</b>
Shipping time	<b>3 days</b>
Number	<b>5906739730049</b>

## Product description

Fast drying acrylic lacquer for painting and renovation of radiators made of steel and cast iron, central heating systems, pipes, boilers etc. Resistant to moisture. Doesn't become yellow, good thermal conductivity, fast drying. Provides smooth, durable surface, you can easy clean.

Heat resistance up to 100°C  
Resistant to moisture and rust  
Creates smooth, glossy surface  
The most popular colour RAL 9016 pure white  
Fast drying time: 10 minutes  
Touch dry: 15-20 min  
Hardened: 16-20 h  
Efficiency 1,5-2 m<sup>2</sup> depending on type of surface by one application  
Hard acrylic film resistant to water and abrasion  
For indoor and outdoor use  
Capacity 400 ml

### Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

### Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

### How to use:

Don't use any priming paint previously. You can easily cover already painted surface by any other paint. Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

