Data current as of: 28-11-2026 18:54

Link to the product: https://pokolimited.co.uk/rust-blocker-4in1-protective-coating-for-metal-p-23.html



Rust Blocker 4in1 - protective coating for metal

Price	**9.49 GBP**
Availability	**Always on stock**
Shipping time	**3 days**

Product description

4in1 properties:

1. Perfect adhesive primer
2. Active corrosion protection technology LCI (blocks process of oxidation)
3. Fast drying paint with exceptional covering power
4. Effective protection against environmental influences

Notice:

360° FUN nozzle allows applying in different positions by wide and narrow stream

LCI Technology - Liquid Corrosion Inhibitor.
For directly usage on rust or old paint coatings.
Active rust protection system prevents corrosion process and it’s further spread.
Protects against environmental influences.
Short drying time up to 8 minutes!
Touch dry: 15-20 min; Hardened: 10-14 h.
Efficiency 1,5-2 m² depending on colour and type of surface by one application.
Heat resistance up to 100°C.
8 colours offer in RAL system in satin finish.
Matt finish
For indoor and outdoor use.
Capacity 400 ml.

Usage:

Before applying read carefully instructions on the container and use according to the manufacturer’s recommendations.

Recommended substrate conditions:
Don’t use any priming paint.
Do not cover already painted surface by any other paint.
Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

How to use:

Don’t use any priming paint previously. Do not cover already painted surface by any other paint. Apply product at

temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.



This product has additional options:

Color: RAL 3000 Red , RAL 6005 Green , RAL 7011 Grey , RAL 7016 Anthracite , RAL 7035 Grey light , RAL 8017 Brown , RAL 9005 Black , RAL 9006 Aluminium , RAL 9010 White

Color chart


RAL 3000 Red
RAL 6005 Green
RAL 7011 Grey
RAL 7016 Anthracite
RAL 7035 Grey Light
RAL 8017 Brown
RAL 9005 Black
RAL 9006 Aluminium
RAL 9010 White