

Link to the product: <https://pokolimited.co.uk/zinc-metallic-p-25.html>



Zinc Metallic

Price	9.99 GBP
Availability	Always on stock
Shipping time	3 days
Number	5906739726714

Product description

Fast drying aluminium-zinc preparation for protection of damaged galvanized structures and their parts in welds or sheets cutting. Used for maintenance of aluminium profiles. Suitable for galvanized surfaces before and after matching. High gloss finish.

Notice:

Using primers is not recommended. Possibility of applying other coating. Compatible with all paint systems (alkyd, acrylic, nitro-combination) water and solvent based.

Perfect cathodic protection against corrosion (aluminium content)
Perfect adhesion to non-ferrous metals and iron
Resistance to high temperatures up to 500°C
Weather conditions resistance
Spot welding ability
Short drying time: 10-15 min
Touch dry: 30-40 min; Hardened: 24 h
Efficiency 1,5-2 m² depending on type of surface by one application
Basic colour: aluminium with high gloss finish
For indoor and outdoor use
Capacity 400ml

Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

Recommended substrate conditions:

Preparing the substrate is very important action influencing the quality and life of varnish coating. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

How to use:

Apply product at temperature about 10 - 25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the

varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimetres. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.



This product has additional options:

Capacity: 600ml , 400ml (- 1.00 GBP)