

Link to the product: <https://pokolimited.co.uk/zinc-primer-p-26.html>



## Zinc Primer

Price	<b>8.99 GBP</b>
Availability	<b>Always on stock</b>
Shipping time	<b>3 days</b>
Number	<b>5906739720699</b>

### Product description

Preparation with high content of zinc (97%). Designed to protect the surface made of metal and steel. Perfect for small craft works such as welding. In industry: rust protection of all structures. Perfect primer for installations exposed to water and hard weather conditions.

Deep matt finish because of high zinc content.

#### Notice:

Compatible with all paint systems (alkyd, acrylic, nitro-combination) water and solvent based.

Creates hard coating which contains 97% of pure zinc

Anticorrosive properties

Weather condition and UV resistance

Resistant to high temperatures up to 300°C

Spot welding ability

Short drying time: 10-15 min

Touch dry: 30-40 min; Hardened: 24 h

Efficiency 1-1,5 m<sup>2</sup> depending on type of surface by one application

Basic colour: grey matt

For indoor and outdoor use

Capacity 400 ml

#### Usage:

Before applying read carefully instructions on the container and use according to the manufacturer's recommendations.

Recommended substrate conditions:

Preparing the substrate is a very important action influencing the quality and life of varnish coating. Fundamental principles, which relate to all surfaces prepared for painting, is to grind, degrease and dry out. After drying the primed surface should be grinded with fine-grained sandpaper (e.g. P600).

#### How to use:

Don't use any priming paint previously. Do not cover already painted surface by any other paint. Apply product at temperature about 10-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, which will help mix the varnish by the ball found inside. Perform the test spray. Apply the varnish with few thin

---

layers rather than one thick layer, from the distance of 25-30 centimeters. Following applying each layer, wait a few minutes. Following the completion, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.

This product has additional options:

**Capacity:** 600ml , 400ml (- 1.00 GBP )